



Hefei Wenhao Bearing Co., Ltd.

HSR25A[1,2,3,4,5,6,7,8,9][D
D,DDHH,KK,KKHH,LL,RR,SS,
SSHH,UU,ZZ,ZZHH]+[97-3000/1]L
THK Standard Linear Guide Accuracy and
Preload Selectable HSR Series

Bearing No.
HSR25A[1,2,3,4,5,6,7,8,9][DD,DDHH,KK,
KKHH,LL,RR,SS,SSHH,UU,ZZ,ZZHH]+[97-30
00/1]L

HSR25A[1,2,3,4,5,6,7,8,9][DD,
DDHH,KK,KKHH,LL,RR,SS,SSHH,
UU,ZZ,ZZHH]+[97-3000/1]L Bearing 2D
drawings and 3D CAD models

Days to Ship	3 Days
Block Type	[Wide] A: Flanged w/Tapped Holes (Obsolete)
The number of LM blocks combined with a axis	1 ~ 9
Nominal Part Number	25
Rail Width W1	23 mm
Material	Carbon Steel
Mounting Height M	36 mm
Rail Length L	97 ~ 3000 mm
Radial Clearance	Normal
Accuracy Grade	Normal Grade (Best Leadtime)
Retainer	N/A
Rolling Element	Ball
Basic Load Rating Dynamic Rating C(N)	27600
Basic Load Rating Static Rating Co(N)	36400
Allowable Static Moment MA(N m)	324
Allowable Static Moment MB(N m)	324



Hefei Wenhao Bearing Co., Ltd.

Allowable Static Moment MC(N m)	366
Symbols for Dust Resistance	SS: End and Side Seals (Best Leadtime) / UU: End Seals
Advanced Seal Options (Longer Leadtime)	DD: Double End Seals and Side Seals / DDHH: DD + Laminated Contact Scraper LaCS / KK: DD + Metal Scraper / KKHH: KK + Laminated Contact Scraper LaCS / LL: Low Resistance End Seal / RR: Low Resistance End + Side Seal / SSHH: SS + Laminated Contact Scraper LaCS / ZZ: SS + Metal Scraper / ZZHH: ZZ + Laminated Contact Scraper LaCS
Block external dimension W	70 mm
Block external dimension L	83.1 mm
Mounting hole for blocks	Tapped Holes
Number of Block Mounting Holes(holes)	4
Mounting Hole Dimension S(M)	M8
Mounting Hole Screw Depth	Through mm
Block dimension L1	59.5 mm